









AERATED CONCRETE / GYPSUM BLOCK



TYPE OF LOAD	MEDIUM & LIGHTWEIGHT LOADS							
	EPOMIX	SYSTEM C-MIX C-MIX 3000	NYLONG	JETFIX	DRIVA	DRIVA LD	NYL	ARPCN
ANCHOR TYPE	 CHEMICAL TYPE	 CHEMICAL TYPE NOT IN UK	 LIGHTWEIGHT TYPE	 LIGHTWEIGHT TYPE NOT IN UK	 -	 -	 LIGHTWEIGHT TYPE	 LIGHTWEIGHT TYPE NOT IN UK
RANGE	M8-M12	M8-M12	Ø 10	SEE PRODUCT PAGE	SEE PRODUCT PAGE	SEE PRODUCT PAGE	Ø 5 - Ø 14	Ø 6 - Ø 8
RECOMMENDED LOAD								
TENSILE N_{rec}^* (kN)	-	CARRY OUT	0.23	0.14*	0.06*	0.046*	0.04*-0.3*	-
SHEAR V_{rec}^* (kN)	-	SITE TESTS	0.23	0.32*-0.46*	0.16*	0.15*	0.032*-0.22*	-
SELECTION CRITERIA	• Static loads	●	●	●	●	●	●	●
	• Stud fixing, male fixing	●	●					
	• Socket fixing, female fixing	●	●		●	●	●	●
	• Immediate loading			●	●	●	●	●
	• Through-fixing	○		●				
	• Metal anchor					●		
	• Stress free in base material	●	●			○	○	

- Suitable
- Possible use
- To be checked by site suitability tests (SPIT technicians are at your service)

* Indicative values

