



Code	Description	Thread/Drill Ø	Fixture thickness	Overall length	Per pack	Price per 100
05427	6 - 20	6	20	55	100	112.40
05429	8 - 30	8	30	70	100	161.10
05436	8 - 60	8	60	100	100	165.00
05430	8 - 90	8	90	130	100	169.00
05431	10 - 10	10	10	60	50	237.00
05432	10 - 45	10	45	95	50	274.40
05437	10 - 70	10	70	120	50	291.80
05433	12 - 10	12	10	70	25	378.80
05434	12 - 40	12	40	100	25	421.60
05435	12 - 80	12	80	140	25	525.80
05447	16 - 10	16	10	90	25	732.40
05448	16 - 45	16	45	125	25	912.60
05495	20 - 20	20	20	120	10	1411.00
05496	20 - 60	20	60	160	10	1611.00

Recommended loads (kN)

Thread Ø	Embed depth mm	Max install torque Nm	Concrete strength C20/25	
			Tensile	Shear
M6	35	10	1.7	3.1
M8	40	20	2.5	5.7
M10	50	45	3.8	9.1
M12	60	65	5.5	13.2
M16	75	120	7.6	24.5
M20	95	180	10.3	38.3



Code	Description	Thread/drill Ø	Fixture thickness	Overall length	Per pack	Price per 100
05500	6 - 10	6	10	50	100	33.60
05504	8 - 10	8	10	50	100	54.00
05506	8 - 50	8	50	90	100	58.60
05509	10 - 10	10	10	60	100	62.00
05511	10 - 45	10	45	95	100	74.00
05513	12 - 10	12	10	70	50	85.40
05514	12 - 40	12	40	100	50	102.60
05515	12 - 80	12	80	140	50	123.70
05520	16 - 10	16	10	90	25	222.00
05521	16 - 45	16	45	125	25	226.00
05522	16 - 95	16	95	175	10	270.00

Recommended loads (kN)

Thread Ø	Embed depth mm	Max install torque Nm	Concrete strength C20/25	
			Tensile	Shear
M6	35	10	1.7	2.9
M8	40	20	2.5	5.3
M10	50	45	3.8	8.4
M12	60	65	5.5	11.3
M16	75	120	7.6	21.0
M20	95	180	10.3	27.3