



Loose bolt version

Code	Description	Thread Ø	Drill Ø	Fixture thickness	Min. drill depth	Per pack	Price per 100
07130	LB 6 - 12/10	6	12	10	60	50	83.20
07131	LB 6 - 12/25	6	12	25	60	50	85.60
07133	LB 8 - 14/10	8	14	10	65	50	106.40
07134	LB 8 - 14/25	8	14	25	65	50	132.90
07136	LB 10 - 16/10	10	16	10	75	50	139.90
07137	LB 10 - 16/25	10	16	25	75	50	163.10
07138	LB 10 - 16/50	10	16	50	75	50	210.80
07139	LB 10 - 16/75	10	16	75	75	50	216.30
07140	LB 12 - 20/10	12	20	10	90	25	241.00
07141	LB 12 - 20/25	12	20	25	90	25	247.00
07124	LB 16 - 25/15	16	25	15	135	5	625.20
07125	LB 16 - 25/30	16	25	30	135	5	646.40



Projecting bolt version

Code	Description	Thread Ø	Drill Ø	Fixture thickness	Min. drill depth	Per pack	Price per 100
07147	PB 8 - 14/15	8	14	15	65	50	108.40
07148	PB 8 - 14/30	8	14	30	65	50	110.80
07149	PB 8 - 14/50	8	14	50	65	50	111.30
07151	PB 10 - 16/15	10	16	15	75	50	134.90
07152	PB 10 - 16/35	10	16	35	75	50	142.20
07153	PB 10 - 16/60	10	16	60	75	25	151.80
07155	PB 12 - 20/15	12	20	15	90	25	212.20
07156	PB 12 - 20/35	12	20	35	90	25	226.60



Shield only version

Code	Description	Thread Ø	Drill Ø	Min. drill depth	Per pack	Price per 100
07348	M 6 - 12 Shield	6	12	60	50	55.00
07349	M 8 - 14 Shield	8	14	65	50	71.80
07350	M 10 - 16 Shield	10	16	75	50	91.20
07351	M 12 - 20 Shield	12	20	90	50	139.80
07352	M 16 - 25 Shield	16	25	135	25	452.20

Recommended loads (kN)

Thread Ø	Anchor type	Embed depth mm	Max install torque Nm	Concrete strength C20/25	
				Tensile	Shear
M6	LB	37	10	3.0	2.4
M8	PB	42	15	3.9	2.8
	LB		25		4.3
M10	PB	52	30	5.3	4.5
	LB		50		6.9
M12	PB	62	50	7.7	6.5
	LB		80		10.1
M16	LB	96	120	18.3	18.7