



SLEEVE ANCHOR

HIGH PERFORMANCE



Loose nut BZP

Code	Description	Thread Ø	Drill Ø	Fixture thickness	Overall length	Per pack	Price per 100
96400	HPS 3 - 6.5/6	3/16"	6.5	6	35	100	22.50
96401	HPS 3 - 6.5/28	3/16"	6.5	28	57	100	27.80
96402	HPS 4 - 8/6	1/4"	8	6	38	100	29.10
96403	HPS 4 - 8/32	1/4"	8	32	64	100	34.50
96404	HPS 5 - 10/10	5/16"	10	10	47	50	37.10
96405	HPS 5 - 10/39	5/16"	10	39	75	50	50.50
96406	HPS 6 - 13/10	3/8"	13	10	53	25	57.20
96407	HPS 6 - 13/28	3/8"	13	28	71	25	67.80
96408	HPS 6 - 13/54	3/8"	13	54	100	25	83.60
96409	HPS 8 - 16/6	1/2"	16	6	57	25	95.60
96410	HPS 8 - 16/57	1/2"	16	57	108	10	132.80
96411	HPS 8 - 16/93	1/2"	16	93	144	10	178.00
96412	HPS 10 - 19/45	5/8"	19	45	100	10	219.20
96413	HPS 10 - 19/105	5/8"	19	105	160	10	279.00

Safe working loads (kN)

Thread Ø	Embed depth mm	Max install torque Nm	Concrete strength 28N/mm ²	
			Tensile	Shear
3/16"	29	6	2.2	1.2
1/4"	34	15	2.7	2.7
5/16"	35	33	4.5	3.5
3/8"	47	57	6.7	5.0
1/2"	51	85	9.2	7.5
5/8"	55	120	11.0	12.7