



### Ø4.8mm anchors supplied with 1 'D' end drill bit per box

Hex head code	Description	Csk head code	Description	Overall length	Max thick to fix	Price per 100
89101	3H32	89100	3F32	32	7	11.30
89103	3H45	89102	3F45	45	20	12.50
89105	3H57	89104	3F57	57	32	13.90
		89106	3F70	70	45	14.60
		89108	3F82	82	57	15.90
		89111	3F100	100	75	17.90



### Ø6.3mm anchors supplied with 1 'D' end drill bit per box

Hex head code	Description	Csk head code	Description	Overall length	Max thick to fix	Price per 100
89113	4H32	89112	4F32	32	7	14.10
89115	4H45	89114	4F45	45	20	16.00
89117	4H57	89116	4F57	57	32	18.00
89119	4H70			70	45	19.60
89121	4H82	89120	4F82	82	57	21.20
		89124	4F100	100	75	23.60
		89126	4F125	125	100	48.90

### SDS drill bits with hex shank insert for anchor setting

Code	Description	To suit anchor length	Price each
89143	Ø 4.8 x 135mm	32, 45, 57	8.65
89144	Ø 4.8 x 160mm	70, 82	8.75
89145	Ø 4.8 x 180mm	100	10.40
89150	Ø 6.3 x 135mm	32, 45, 57	8.65
89151	Ø 6.3 x 160mm	70, 82	8.75
89152	Ø 6.3 x 180mm	100	10.40

### Installation equipment

Code	Description	Price each
88205	Condribe 1000 kit	33.50


### Ultimate failure loads (kN)

Type	Embed depth mm	Tensile Substrate	
		40N/mm <sup>2</sup> concrete	Typical hollow concrete beam
Ø4.8mm	25	2.63	4.67*
	40	5.65	9.24*
Ø6.3mm	25	6.00	5.81*
	40	11.80	10.37*

\* Applicable min. embed depths in hollow concrete beam are 27mm hollow pot and 32mm solid web.



Code	Description	Drill Ø	Collar length	Screw req.	Per pack	Price per 100
97450	TB3812	8	11.1	32mm + fixture	100	16.20



Code	Description	Drill Ø	Overall length	Per pack	Price per 100
97429	Ø6 x 30	6	30	100	14.70
97430	Ø6 x 50	6	50	100	19.00